



Garmin GTN 650 Workshop

VFR & IFR Operations


Presentation Outline

- Basic 650 Operations
 - GTN 650 Overview
 - Start-Up Screens
 - Interface Basics
 - Terrain Awareness
 - Traffic & Weather
 - Information & Waypoints
 - "Nearest"
 - Useful Features
 - Computing Winds Aloft
 - Vertical Navigation
 - OBS
 - Visual Approaches
 - Communication
 - Flight Plans
 - Database Currency
- VFR Demonstrations

- GPS Do's and Don'ts
- IFR Operational Requirements
- IFR Operations
 - More Flight Plans
 - Loading Approaches
 - Multiple Destinations
 - SIDs and STARs
 - GPS Approach Modes
 - GPS Substitutions
 - Suspend Mode
- IFR Demonstrations
 - KDXR -> KGON (GON ILS Rwy 5)
 - OXC RNAV (GPS) Rwy 18
 - MMK GPS Rwy 36
- IFR Do's and Don'ts


GTN 650 Overview

Database Verification



- Displays GTN software versions
- Displays installed databases and their expiration dates
 - Expired databases will be shown in yellow
 - "Navigation" database required to be current for IFR flight*
 - All other databases are optional for VFR and IFR flight

Instrument Panel Self-Test



Verify CDI / GS displacement is correct

- CDI (LCDI) half left
- ▶ G/S (VCDI) half up
- To/From is TO
- No flags

Verify OBS course


- Garmin "OBS" value and selected OBS course should match
 - Should be within 2 degrees
- ▶ The GTN is not legal for IFR navigation if any of the self-tests fail





Default Nav Page

- Press and hold HOME to load from any page
 - Or access it from the Home page
- ▶ It's where the CDI and OBS functions are controlled from
- Provides a shortcut button to enter the moving map page





GTN 650 Home Page

The Home page is where you access all of the features of the 650



GTN 650 Navigation

▶ NAV group

- How do I get to my destination?
- Are there any hazards on the way (traffic, terrain, weather)?

WPT group

- Where am I going, and what is available there?
- The "AFD" section of the Garmin

AUX group


- Flight planning and E6B-like utilities
- System setup

NRST group

What is nearest to my current location?



GTN 650 Key Functions



User Input

▶ FastFindTM input is predictive – it automatically fills in the nearest matching waypoint as you type.











Map Panning & Selection

- Can be used to move the map beyond its current limits without adjusting the zoom level
- Can also be used to select a point on the map to get bearing and distance information, as well as the name of the selected point



- Press Direct-To to navigate direct to a highlighted point
- Touch "Waypoint Info" to load more information on the point
- Touch "Create Waypoint" to add a point in space as a userdefined waypoint





Map Declutter



- There are 4 user-selectable map detail levels
 - All data shown
 - 2. Removes all land data except rivers & lakes.
 - 3. Removes all airspace except Prohibited & Restricted. Also removes NDBs, Intersections, and User waypoints.
 - 4. Removes all data except the Active Flight Plan, Airways, rivers, lakes, traffic, and lightning data.





Map Orientation



- Three modes of map orientation
 - North up
 - Orientation of paper charts
 - Track up
 - Current ground track is straight up
 - Heading up
 - Current heading is straight up
- From the "Map" screen, touch "Menu", select "Map Setup", then "Orientation"

Terrain Awareness





Terrain Awareness


- Portrays a 2D picture of the surrounding terrain and obstacles relative to the position & altitude of the aircraft
 - ▶ Based off of GPS altitude, converted to MSL
- Advisory-only but very useful when flying in hilly areas, especially at night
 - Non-TSO-C151b terrain awareness system
- Separate terrain database updates
 - Obstacle and terrain databases are updated at different intervals than the nav data







Terrain Coloring



Terrain more than 1000 ft below the aircraft altitude (Black)

- Color coding applies to terrain and top of obstacles
- Can be displayed on the <u>moving map</u> or a dedicated <u>terrain page</u>







TAWS Alerts

Alert Type	Alert Annunciation	Aural Message
Excessive Descent Rate Warning (EDR-W)	PULL UP	"Pull Up"
FLTA Terrain Warning (RTC-W, ITI-W)	PULL UP	"Terrain Ahead, Pull Up; Terrain Ahead, Pull Up"* or "Terrain, Terrain; Pull Up, Pull Up"
FLTA Obstacle Warning (ROC-W, IOI-W)	PULL UP	"Obstacle Ahead, Pull Up; Obstacle Ahead, Pull Up" * or "Obstacle, Obstacle; Pull Up, Pull Up"
FLTA Wire Warning (ILI-W, RLC-W)	PULL UP	"Wire Ahead Pull Up, Wire Ahead Pull Up"
FLTA Terrain Caution (RTC-C, ITI-C)	TERRAIN	"Terrain Ahead; Terrain Ahead"* or "Caution, Terrain; Caution, Terrain"
FLTA Obstacle Caution (ROC-C, IOI-C)	OBSTCL	"Obstacle Ahead; Obstacle Ahead" * or "Caution, Obstacle; Caution, Obstacle"
FLTA Wire Caution (ILI-C, RLC-C)	WIRE	"Wire Ahead"
Premature Descent Alert Caution (PDA)	TERRAIN	"Too Low, Terrain"
Excessive Descent Rate Caution (EDR-C)	TERRAIN	"Sink Rate"
Negative Climb Rate Caution (NCR-C)	TERRAIN	"Don't Sink"* or "Too Low, Terrain"
Voice Call Out (VCO-500)	None	"Five-Hundred"

Hard Warning – Take evasive action immediately

- I. Apply full power
- Retract speed brakes (if applicable)
- 3. Pitch for best climb angle (Vx)
- 4. Leave flaps & gear alone until clear

Soft Alert – Check your situational awareness and take action if necessary to avoid a collision

<u>Informational</u> – "Configured, stabilized, cleared to land Rwy XX". Otherwise, go around.

Traffic & Weather Pages



Traffic Page

- Displays the 8 nearest targets within a specified filter range
 - Two modes:
 - Relative vector
 - motion relative to you
 - Absolute vector
 - □ target's ground track
- Traffic data can also
 optionally be shown on
 the moving map page




- Traffic Advisory (TA) Traffic may pose a collision threat.
- Proximity Advisory (PA) Traffic Is within 5nm and +/- 1,200'
- Other detected traffic



Weather Page

- From the "Home" screen, select "Weather" and then "FIS-B Weather"
- Displays NEXRAD radar, graphical METARs, TFRs, AIRMETs/SIGMETs, and PIREPs
- Weather data (radar, stormscope, and METARs)
 can also optionally be shown on the moving map page

















Textual Weather Pages

- From the "Map" or "Weather" page, touch the location you want more information on.
- You can also select "WX Data" from the airport information screen.







Information & Waypoints





"Nearest" Pages

- Provides
 - Airports
 - Waypoints
 - Intersections
 - ▶ NDBs
 - VORs
 - User Waypoints
 - Airspace & Services
 - ▶ ARTCC
 - ▶ FSS
 - Airspace
- Can load information about each waypoint/airspace





Waypoint Info

- Waypoint info is available for:
 - Airports
 - Intersections
 - VORs/NDBs
 - User waypoints
- From the waypoint info page, you can...
 - …load an approach procedure for the airport
 - …load the comm/nav frequency for the waypoint to STBY
 - ...go Direct-To the loaded waypoint











User-Defined Waypoints

- Up to 1000 user-defined waypoints can be stored
- User waypoints are referenced by name only
- User waypoints are best used for ground references (houses, etc) or common reporting points (e.g. "the prison" at KDXR)











User-Defined Waypoints

- Can be created from the User Waypoint page, from the Map page, or from the Direct-To & FPL pages
 - When created from the Direct-To or FPL page, the waypoint will use the aircraft's current position
- NOTE: User-waypoints will also be created automatically if you upload a flight plan (via Connext) that contains a waypoint not in the 650's database







Useful Features & Tips





Computing Winds Aloft




- Great tool to use when submitting a PIREP
- "Ind Alt" will initially show your GPS altitude
 - Will likely need fine tuning, but not by much
- "CAS" will initially show your GPS ground speed
- "BARO" will show the last entered value
- "HDG" will show your GPS ground track heading
 - This should be set to your magnetic heading

VCALC







VNAV





- I) Have an active flight plan
- 2) Set a waypoint altitude constraint
 - l) At, At or Above, At or Below, Between
 - 2) Altitude/Altitude Range
 - 3) Before, After*
- 3) Tap "Save"
- 4) [Optional] Set VS Target/FPA (Default: -3° FPA)












The OBS/SUSP/UNSUP Button

Enroute

- Disables waypoint sequencing past the current waypoint
- Turns the current waypoint into a virtual VOR
 - You can select any radial off the waypoint
- Approaches & Holds
 - Changes to SUSP/UNSUSP
 - Suspends or unsuspends waypoint sequencing





Visual Approaches & Runway Centerlines





NOTE: An airport must be the last waypoint in the flight plan for this feature to be available!

Visual Approach

- Available within a preconfigured distance from the destination airport (default is 10nm)
- Provides advisory lateral (and at some airports, vertical) guidance to any runway
 - A 3nm final approach marker is also provided

Runway Centerlines

Displayed for all runways at the destination airport



Communication

Emergency Frequency

 Press and hold the volume knob for approximately 2 seconds



Comm. Monitoring

- Receive/transmit on active frequency and simultaneously monitor standby frequency
 - Tap on the Standby frequency
 - 2) Select "MON"
 - 3) Tap "Enter" to close screen



White vs Cyan text -or- green MON, denotes frequency monitoring is active



Flight Plans

VFR & IFR



When Your Database is Not Current


VFR

No legal requirements to have a current database

IFR

- Legal for en-route and terminal navigation
 - Each waypoint must be verified with an alternate source of current data (e.g. paper chart, electronic chart)
- Per the Garmin 650 STC, "GPS", "or GPS", and "RNAV (GPS)" approaches are <u>not</u> allowed
 - Example: Danbury's "GPS RWY 08" approach is not allowed, but something like a "VOR or GPS-A" approach is allowed if flown using VOR guidance.
 - Danbury's "LOC RWY 08" is also allowed





Flight Plans

- Up to 99 stored flight plans
 - Up to 100 waypoints per flight plan
 - Custom names of up to 18 alpha/numeric characters
- Supports victor airways










Activating a Leg

- I. Go to the flight plan page
- Select the waypoint where the leg ENDS
- 3. Select ACTIVATE LEG









Holds

- Go to the flight plan page & select the holding waypoint
- Select Hold at WPT
- Configure & preview the hold

DIS / ETA

ALT

Load the hold

🖄 KDXR / KGON





Garmin Aviation Trainer



- PC Trainer
 - Windows 7 or later
 - macOS not supported
- ▶ iPad Trainer
 - ▶ iPad 2 or newer



VFR GPS Demonstrations

- I. Start-up screen: Database currency
- 2. Home page
- 3. Interface navigation basics
- 4. Changing data fields on the map page
- 5. Map setup
- 6. Terrain awareness
- 7. Looking up waypoint/airport information
 - Entering data
- 8. "Nearest" demonstration
- 9. Scheduler and flight timers
- 10. Computing winds aloft
- **11.**Vertical navigation



GPS Do's and Don'ts



DO

- Develop skills in stages
- Practice with PC/iPad simulators
- Program on the ground
- Delegate GPS operations to copilot
- Fly the airplane first!





- Exceed VFR or personal minimums
- Focus inside the cockpit
- Rely solely on GPS map display for navigation
- Fiddle with it while close to an airport or in a high workload situation
- Try new features for the first time in the air

GPS is Not a Substitute for Sound ADM!! "Proper Prior Planning Prevents Poor Performance!"

VFR Quiz Time!

What is the difference between DTK and BRG?

DTK is the desired course between two waypoints; BRG is the direction from your present position to a waypoint.

How can you visually maintain your DTK to the next waypoint?

Keep the tip of the cyan track vector over the magenta line.

What is the significance of the "V3NM" on a Visual Approach?

It marks a distance of 3NM from the destination airport.

How do you display the default nav page from any screen?

Press and hold the "HOME" button.

What are the two primary methods to select a frequency?

1) Set the standby frequency with the knob, 2) Tap the standby field and directly enter the frequency.

How do you swap frequencies?

Press and hold the right knob, or tap the active frequency.

IFR Operational Requirements

GPS/WAAS Terminology

- SBAS <u>Satellite Based</u>
 <u>Augmentation System</u>
 - WAAS Wide Area
 Augmentation System
 - A type of SBAS
- RAIM Receiver
 Autonomous Integrity
 Monitor
- FDE Fault Detection & Exclusion
- ▶ WFDE WAAS FDE

- ▶ FDE consists of two parts:
 - Fault Detection (RAIM)
 - Detects when an erroneous satellite signal is present
 - 2. Fault Exclusion
 - Excludes the erroneous
 satellite signal so it doesn't
 affect navigational accuracy

Garmin GTN 650 AFMS

- The GTN 650 AFMS (Approved Flight Manual Supplement) governs what operations are allowed or not allowed.
 - "For flight planning purposes, in areas where SBAS coverage is not available, the flight crew must check RAIM availability."
 - <u>Author's interpretation</u>: If there are any NOTAMs for GPS outages or jamming exercises that are along or near the planned route of flight, you must perform a RAIM check prior to flight.
 - □ https://fly.garmin.com/fly-garmin/support/raim/
 - "It is not acceptable to flight plan a required alternate airport based on RNAV(GPS) LP/LPV or LNAV/VNAV approach minimums. The required alternate airport must be flight planned using an LNAV approach minimums or available ground-based approach aid."
 - Translation: If the alternate airport only has GPS approaches, 800-2 minimums must be assumed. 600-2 minimums can only be used if it has an ILS approach.



IFR Operations

Using the GTN 650



Loading an Approach

- Press the "HOME" button
- 2. Tap "PROC"
- 3. Tap "Approach"
- 4. Select the desired approach
- 5. Select the desired transition
 - 1. "Vectors" draws a reference line to the FAF
- 6. "Load" vs "Activate"
 - "Load" adds the approach waypoints to the flight plan, but doesn't activate it.
 - "Activate" also loads the waypoints, but then provides Direct-To course guidance to the initial fix









Cancelling an Approach

- Press the "HOME" button
- Tap "Flight Plan"
- 3. Scroll down to the loaded approach and tap on it
- Select "Remove APPR"
 - The 650 will continue navigating to the last selected waypoint









Loading SIDs and STARs


- Similar method to loading an approach
 - I. Press the "HOME" button
 - 2. Tap "PROC"
 - 3. Tap "Departure" or "Arrival"
 - 4. Select the desired departure / approach
 - Select the desired transition
 - 6. Tap "Load Arrival"/"Load Departure"








GPS Approach Modes





CDI Scale Transitions



During the transition phases, the CDI may give the impression that you are off course, even though you may be on a perfectly good intercept angle.



650 GPS Approach Mode Summary

Annunciation	Approach	Description
LPV	LPV	<u>L</u> ocalizer <u>P</u> erformance with <u>V</u> ertical guidance
LP+V	LP	Non-precision <u>L</u> ocalizer <u>P</u> erformance with <i>advisory</i> <u>v</u> ertical guidance
LP	LP	Non-precision <u>L</u> ocalizer <u>P</u> erformance – allows for lower minimums than LNAV
LNAV+V	LNAV	Non-precision <u>Lateral</u> <u>Navigation</u> with <i>advisory</i> <u>vertical</u> guidance
LNAV	LNAV	Non-precision <u>L</u> ateral <u>Nav</u> igation



Additional 650 GPS Modes

Annunciation	Description	
MAPR	Missed Approach	
	CDI full scale deflection = 0.3 NM	
ENR	En-route navigation	
	CDI full scale deflection = 2.0 NM	
TERM	Terminal area navigation	
	CDI full scale deflection = 1.0 NM	
LOW ALT	For LNAV+V and LPV approaches	
	Indicates the aircraft's estimated height is lower than the FAF height by approximately 50 meters (164 feet). Not active when TAWS is operational.	



Abnormal Modes

- Always check the annunciated approach mode when crossing the FAF!
 - A yellow annunciation (e.g. LPV, LNAV, etc) means you might not have the accuracy needed, and that the mode could degrade.
- If flying a coupled GPS approach and the GPS position becomes degraded, the autopilot state might also change.



GPS Substitutions

- AC90-108 Operational & Airworthiness Guidance
 - Suitable RNAV system as an alternate means of navigation

Allowed substitutions

- Determine aircraft position relative to/distance from a VOR, TACAN, NDB, compass locator, DME fix, fix defined by a VOR radial/TACAN course/NDB bearing/compass locator bearing intersecting a VOR or LOC course
- Navigate to/from a VOR, TACAN, NDB, or compass locator
- ▶ Hold over a VOR, TACAN, NDB, compass locator, or DME fix
- Fly an arc based upon DME
- All of the above is allowed even when a facility is identified as required on a procedure (e.g. "ADF required")

Non-allowed substitutions

- When a procedure is NOTAMed as "not authorized" ("NA")
 - Example: A procedure is based upon a recently decommissioned NAVAID
- Substitution on a Final Approach Segment
- Lateral Navigation on LOC-Based Courses



Vectors to Final

- Provides an extended course direct to the final approach point
- When flying outbound (opposite direction), the GTN will automatically go into SUSP mode
 - Once you start the turn inbound to the FAF, the GTN will automatically unsuspend







Missed Approach

- Upon reaching the MAP, the "Missed Approach Waypoint Reached" screen will pop up
 - "Remain Suspended" to complete the approach
 - "Activate Missed Approach" to begin guidance for the missed approach
- You can also manually activate the missed approach for any GPS approach once inside the FAF
 - HOME, PROC, "Activate Missed Approach"







Suspend Mode

- ▶ GTN suspends automatic leg sequencing when the start of the next leg cannot be determined
 - SUSP = Pilot intervention required
- Two main types of waypoint sequencing suspension
 - Pilot-induced
 - Pilot intentionally suspends waypoint sequencing
 - Navigator-induced
 - Navigator cannot determine when to begin the next leg




Suspend Mode

- Reasons for automatic waypoint suspension
 - The MAP has been reached
 - Does the pilot intend to land, or follow the missed approach?
 - Holding pattern requires pilot action to exit
 - Ex) A hold at the end of a missed approach procedure
 - Leg requires a course/heading to be flown indefinitely
 - Ex) "fly heading 360, expect radar vectors"
 - Leg ends at a specific altitude and baro-corrected input not provided
 - Ex) "climb to 2500, then..."
 - Aircraft flying opposite direction to a vectors-to-final course
 - Temporary navigator will resume sequencing when flying inbound



IFR GPS Demonstrations

- 1. Flight plans
 - I. Creation
 - 2. Saving
 - 3. Loading
- 2. Activating a leg
- 3. Loading and activating an approach
- 4. Loading a SID and STAR
 - KJFK.JFK1.RW04L, VCN8.BRIGS.KPHL



KDXR CMK V3 HFD V58 GON KGON



IFR Do's and Don'ts

DO



- Set higher personal minimums until comfortable with its use
- Check GPS/VLOC CDI indicator often
- Check and ID the active VLOC frequency for ILS/LOC
- Always set the OBS (and heading bug) to DTK
- Pay attention to suspended waypoint sequencing and active waypoint



DON'T

- Use features for the first time in IFR conditions
 - Practice in VFR conditions first
- Rely solely on one nav source
 - DO "shadow" GPS with other systems if available
- Program during high workload situations
- Forget to check the annunciated approach mode prior to the FAF

IFR Quiz Time!

When would the GTN go into SUSP mode when activating Vectors-to-Final?

When must you switch from GPS to VLOC guidance when flying a non-GPS-based approach?

What are some common Mistakes when flying a VOR/LOC/ILS approach?

Can you proceed via IFR to the destination when the INTEG indication is displayed?

What does "Load APPR & Activate" do, compared to "Load APPR"?

When the aircraft is on the "from" side of the FAF. Waypoint sequencing will resume when you are on the "to" side.

Upon reaching the FAF.

Failing to Set CDI VLOC Mode, switch and IDENT VLOC Freq

Yes – Monitor VOR Enroute. The destination must have a non-GPS-based approach.

The active leg becomes a Direct-To to the selected transition waypoint.

More Information

- Garmin Website http://www.garmin.com
 - ▶ GTN 650 manual
 - Garmin Aviation Trainer
 - Training Syllabus
 - Tutorial Videos

- Avweb http://www.avweb.com
- AOPA Air SafetyFoundation –http://www.aopa.org/asf
 - ASF Safety Advisor GPS Technology

Open Sky Aviation, LLC.

http://openskyaviation.biz

gbaluha@openskyaviation.biz



Additional Information

More information for the curious

GPS/WAAS Overview


A Brief Review

GPS and WAAS Overview

- Global Positioning System (GPS)
 - Satellite-based navigation
 - > 24 satellites orbiting 12,000 miles above the earth's surface
 - Satellites orbit twice a day in a precisely-known orbit
 - Full constellation became operational in 1994
 - Receivers use time-based triangulation to calculate the user's location
 - Accurate within 15 meters (~50 feet)
- Wide Area Augmentation System (WAAS)
 - Corrects for GPS signal errors
 - Consists of a network of ground reference stations at precisely-surveyed locations.
 - A master station generates a correction signal and transmits it to one of two
 geostationary satellites
 - Available in the entire Continental US and parts of Canada and Mexico
 - Improved position accuracies
 - ▶ I meter (~3 feet) horizontal
 - → 2 meters (~6 feet) vertical

GPS Timeline

- ▶ 1995: GPS Selective Availability (SA)
 - ▶ 330 990 feet
- 2000: SA Turned Off
 - ▶ 100 330 feet
- 2003:Wide Area Augmentation System (WAAS) Enabled
 - < 23 feet</p>
 - Provides Vertical Guidance
 - WAAS Approaches Slightly Higher Minimums than Cat I ILS




GPS Navigation Concepts

GPS Navigation Concepts

A course is always defined by two waypoints!

DTK	Desired Track
TRK	Ground Track
BRG	Bearing
CTS	Course To Steer
XTK	Cross-Track
DIS	Distance (nm)
GS	Groundspeed (kts)





What is RAIM?

- Receiver <u>Autonomous Integrity</u>
 <u>Monitoring</u>
 - The "Off" flag Primary means of ensuring receiver integrity
 - Needs a minimum of 5 satellites in view
 - ▶ 6 for FDE (WAAS)
 - Required for IFR operations
 - Handheld GPSes do not normally have RAIM
 - Must be available at the FAF to fly a GPS approach
- "RAIM Prediction" alerts you to RAIM error at destination before you fly


RAIM Prediction is required for any IFR flight that uses RNAV procedures

RAIM not available in flight

- Enroute/Terminal Revert to VOR, or cross-check every 15 minutes
- Prior to FAF Fly to MAP and execute the Missed Approach procedure
- After FAF Expect 5 minutes of GPS guidance

GPS Accuracy vs. VOR

- CDI Comparison
 - ► GPS: Fixed-width accuracy*
 - VOR: Accuracy varies with distance
 - Becomes more sensitive as you get closer
 - "Cone of confusion"
- "Resolver-Type" Design
 - Resolver course indicator coupled to CDI
 - OBS course selector must be set to desired course





Data Fields

GTN 650 User Data Fields

Clockwise from upper-left corner

Moving Map

- ACTV WPT Active Waypoint
 - TRK Track
- DTK Desired Track
- DIS Distance To Waypoint
- GS Groundspeed

Default Nav

- ▶ DIS Distance To Waypoint
- DTK Desired Track
- VSR Vertical SpeedRequired
 - ▶ **BRG** Bearing To Waypoint
- ETE Estimated Time Enroute
- ► TRK Track
- GS Groundspeed


GTN 650 Data Fields (Subset)

- ACTV WPT ActiveWaypoint
- ▶ BRG Bearing To Waypoint
- ▶ DIS Distance To Waypoint
- DFLT NAV Default nav page (lower-right only)
- DTK Desired Track
- ▶ ESA En-route Safe Altitude
- ETA Estimated Time of Arrival
- ETA at Dest

- ETE Estimated Time Enroute
- ▶ GS Groundspeed
- OBS/Susp/Unsusp button (lower-right only)
- ► TRK Track
- Wind Wind Speed and Direction
- Time to TOD Time to Top of Descent
- XTK Cross-Track Error

Utilities

Satellite Status Page






Scheduler & Flight Timers











IFR Concepts

Are You IFR Legal?


- ▶ IFR-Certified GPS Unit
 - ▶ Garmin 650
 - GPS/SBASTSO C-146c Certified for sole source of navigation
- IFR-Certified Installation
 - Installation must also be certified! (AC20-138A)
 - Cockpit Reference Guide must be within reach of the pilot
 - Navigation database current (Updated every 28 days)?*
- IFR Usage
 - May be used in lieu of ADF and DME*
 - Review GPS/WAAS NOTAMs and "All available information" – FAR 91.103
- * = More details provided on a later slide



- Alternate means of navigation required FAR 91.205
- A non-GPS approach must be available at alternate airport (or VFR)
- No longer required with WAAS (TSO C-146a/c)
- IFR RNAV-Capable Aircraft
 - ICAO: B2 (RNAV 5 GNSS), C2 (RNAV 2 GNSS), D2 (RNAV 1 GNSS)

Types of GPS Approaches

- Ist Generation Nonprecision VOR/NDB overlay approaches (RNAV)
 - Many are being replaced by 2nd Gen approaches
- 2nd Generation Standalone non-precision GPS approaches (RNAV)
- 3rd Generation WAAS approach with vertical guidance







Multiple Destinations

Switching approaches

- I. Press "HOME", select "PROC" and then "Approach"
- 2. Tap "Airport"
- 3. Tap "Find", tap "Flight Plan", and select the approach from the list

Reasons

- Easily load an approach for the departure or alternate airport
- Simplify IFR training / proficiency









Old Quizzes

VFR Quiz Time!

What is the difference between HDG and TRK?

What is the CDI mode used for?

What is the OBS mode used for?

How do you cancel a Direct-To course?

How do you display the default nav page from any screen?

How do you swap frequencies?

HDG is the magnetic heading the aircraft is pointed, while TRK is the aircraft's ground track.

To toggle between navigation sources (GPS or VLOC) output to an external HSI or CDI.

It allows the pilot to select a desired course to/from a waypoint (entering the traffic pattern, or holds).

Direct-To, "Remove".

Press and hold the "HOME" button.

Press and hold the right knob, or tap the active frequency.

Wake Up – It's Quiz Time!

Is a non-GPS approach required for an alternate when using the GTN 650?

The alternate has an LPV approach – what alternate minimums apply?

What are some common Mistakes when setting up for an ILS?

True or False: INTEG indication in flight = OK to proceed to destination via IFR

What is the difference between charted and GPS distance?

No longer required with TSO 146a certified GPS/WAAS (sole source navigation)

Non-precision approach minimums (800-2) apply unless otherwise stated

Failure to Set CDI VLOC Mode, Switch and IDENT VLOC Freq

True – Monitor VOR Enroute.

Destination Must Have Non-GPS

Approach

Charted distance is DME slantrange distance, GPS is great-circle ground distance